

NOCTIS LUX 3 30W floodlight



CE

Power	30 W	Voltage	230 V
Luminous flux*	2800 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65



See more on dedicated page [➔](#)



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI029054NW_PW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2800 lm (120°)
Luminous flux**	2800 lm (360°)
Lamp efficacy	93 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	150x110x27 mm
Weight	0.349 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux