


ALGINE ECO 12W downlight



| | | | |
|-----------------|----------------------|---------------------------|---------------|
| Power | 12 W | Voltage | 230 V |
| Luminous flux* | 750 lm (120°) | Colour temperature | 3000 K |
| Colour of light | WW | Beam angle | 120 ° |
| IK | 06 | Degree of protection (IP) | IP20 |




 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|-------------------|
| Code | SLI036024WW |
| Power | 12 W |
| Nominal current | 60 mA |
| Voltage | 230 V |
| Energy efficiency class | G |
| Energy consumption | 12 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.5 |
| Useful luminous flux* | 750 lm (120°) |
| Luminous flux** | 750 lm (360°) |
| Lamp efficacy | 62 lm/W |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 120 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, PLASTIC |
| IK | 06 |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 175x175x35 mm |
| Weight | 0.36 kg |
| For use | Inside |
| Assembly method | On the ceiling |
| Application | INT |
| Made in | PRC |



*applies to the LED source used. **Luminaire luminous flux