


## NOCTIS LUX 3 20W floodlight with motion sensor



CE

Power	<b>20 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2000 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Degree of protection (IP)	<b>IP44</b>



See more on dedicated page 



 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI029049NW_CZUJNIK_PW
Power	20 W
Nominal current	90 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2000 lm (120°)
Luminous flux**	2000 lm (360°)
Lamp efficacy	100 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	120x170x53 mm
Weight	0.296 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux