


NYPHEA 36W CCT plafond SPECTRUM SMART




Power	36 W	Voltage	230 V
Luminous flux*	2840 lm (120°)	Colour temperature	2700-6500 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP20		



 User manual




 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI031032CCT
Power	36 W
Nominal current	165 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2840 lm (120°)
Luminous flux**	2840 lm (360°)
Lamp efficacy	79 lm/W
Colour temperature	2700-6500 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	488x72 mm
Weight	1.87 kg
For use	Inside
Assembly method	On the ceiling
Application	INT
Made in	PRC



*applies to the LED source used, **Luminaire luminous flux

*Luminaire with the ability to change the color of light (2700 - 6500K) or dimming by application Spectrum SMART.