




CE

Power	<b>20 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1820 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>100 °</b>
Protection class	<b>IP44</b>		



See more on dedicated page 




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI029042NW_CZUJNIK
Power	20 W
Nominal current	100 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	1820 lm (120°)
Luminous flux**	1750/1820 lm (360°)
Light efficiency	88 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, GLASS
Protection class	IP44
Colour	White
Dimension (axbxc)	158x121x25 mm
Weight	0.3 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux

Motion sensor PIR (sensor regulated, range: 2-10 m., operating time: 10 s. - 7 m., ambient light: 3 - 2000 LUX)