





Power	18 W	Voltage	230 V
Luminous flux*	1900 lm (120°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	110 °
IK	06	Protection class	IP20




See more on dedicated page 



 User manual



 Declaration of Conformity




 Photometric file



Technical data:

Product code	SLI037029NW
Power	18 W
Nominal current	134 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	1900 lm (120°)
Luminous flux**	1900 lm (360°)
Light efficiency	106 lm/W
Luminous intensity	670 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	223x35 mm
Mounting hole	o200 mm
For use	Inside
Assembly method	surface mounted, recessed
Application	wew
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux