


LED15 SMD MR16


Lampa z diodami LED / LED lamp



LED15 SMD MR16



rozsył światła / light distribution
 $\Delta = 120^\circ$



E(0°) - max natężenie w osi wiązki / max intensity in beam axis

Kanlux	Kanlux	Tc [K]
LED15 SMD MR16-WW	08942	2900-3500
LED15 SMD MR16-CW	08943	6200-6800

12V DC, 2,5, 2,5-22, 15 LED SMD, Gx5,3, 210, 120, Ra ≥80, 20000, A+, 1/10/100, 40, CE


źródło wykorzystuje diody LED SMD 5050 / light source uses SMD 5050 LEDs

LED24 SMD MR16

Lampa z diodami LED / LED lamp



LED24 SMD MR16



	Kanlux	Kanlux	(W)	Tc [K]	[lm]
NEW	LED24 SMD MR16-WW	18473	3 - 26	2700-3200	270
NEW	LED24 SMD MR16-CW	18472	3 - 28	5700-6300	300

12V AC/DC, 3, 24 LED SMD, Gx5,3, 120, Ra ≥75, 30000, >15000, A+, 1/10/100, 40, CE

źródło wykorzystuje diody LED SMD 5050 / light source uses SMD 5050 LEDs